

# 3MP CX30p

- 14Bit 14-Bit LUT
- LED LED Backlight
- HB High Brightness
- SBC Self-Brightness Control (SBC)
- LUC Luminance Uniformity Control
- IQSensor DICOM Sensor (IQ Sensor® II)
- DAC Digital Ambient Control (DAC)
- Pivot Pivot
- Multi function Stand-base Multi-functional Stand-base
- DVI DVI Input Connectivity
- DP Displayport




**WIDE**

The CX30p display, optimized for PACS, CT, MR and US viewing, is the new medical imaging display solution with highly advanced LED backlight technology; higher brightness, better contrast ratio, real black uniformity performance and perfect image quality in color. Color images can be viewed with the comfort of preset DICOM-modes, enabling to review images from different medical sources in optimal conditions, improving efficiency and diagnostic performance significantly.

# CX30p 3 Mega-pixel Color Diagnostic Display

- Ultra High Brightness
- LED Backlight
- 14-Bit LUT
- IQ-Sensor® / SBC Sensor



A better image quality can make a life critical difference when it comes to making a diagnosis. WIDE has developed this display to produce the highest-quality images and most comprehensive tools, because every life is precious.

Panel	TFT AMLCD IPS Color
Native Resolution	2048(H) x 1536(V)
Pixel Pitch	0.210mm x 0.210mm
Active Display Area	431.6m x 323.7mm (17.0"x12.7")
Active Screen Size (Diagonal)	539.5mm (21.2")
Viewing Angle(Typ)	170°,170° at 50:1 Contrast Ratio
Brightness Max.(Typ)	900cd/m <sup>2</sup>
Brightness Calibrated (Typ)	450cd/m <sup>2</sup>
Contrast Ratio (Typ)	1,400:1
Bit Rate for Look-Up Table	14-bit
Digital Video Input	DVI-D, Display Port
Display Communication	DDC2B (VESA Standard Compliance)
Universal Serial Bus (USB)	1 up and 3 down-streams
Power Supply	AC Input 100-240Volt+/-10%, 60Hz/50Hz+/-3Hz
Built-in Sensors	IQ Sensor II®, SBC, DAC
Display Adjustments	Source, Menu, Enter, Up/Dn, Lamp, Power
OSD Languages	English, German, French, Spanish, Italian, Russian, Japanese, Chinese, Korean
Power Consumption	Max: 85W, Typ: 51W, Power Save: 1W
Tilt/Swivel/Height Adjustments	-3°,+15°/±20°/110mm
Portrait/Landscape Rotation	90° (Counter clockwise)
Mounting Hole	VESA Standard (100mmx100mm)
Weight	11.5kg(25.4lb) with Stand
Dimension	378mm(W) x 535.9mm(H) x 248.8mm(D)
Operational Temperature	0°C to 40°C (32°F to 104°F)
Operational Humidity	10% to 80%
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Certifications and Standards	FCC Class B, CE, VCCI Class B, KC, ICES-003-B, C-Tick, UL60601-1, CSA Std., C22.2, No.601.1, IEC/EN60601-1, FDA510(k)
Option	Protect Glass

## Contact

**WIDE KOREA** (Gomae-Dong) 12 Wongomae-Ro, Giheung-Gu, Yongin-Si, Gyeonggi-Do 446-901, Korea Tel: +82-31-218-1600 Fax: +82-31-274-7400 info@widecorp.com

**WIDE USA** 8 Hammond St., Suite #114 Irvine, CA 92618, USA Tel: +1-949-305-9933 Fax: +1-949-305-5452 infousa@widecorp.com

**WIDE EUROPE B.V.** Panamalaan 3L, 1019 AS Amsterdam, The Netherlands Tel: +31 20 311 9797 Fax: +31 20 311 9790 infoeu@widecorp.com

**WIDE JAPAN** Shinjuku Suzuki Bldg A 1-6-8 Shinjuku, Shinjuku-Ku, Tokyo 160-0022, Japan Tel: +81-3-6457-8371 Fax: +81-3-6457-8372 infojapan@widecorp.com

**WIDE ASIA** 1350/88-89, Thairong tower, Pattanakarn road, Suanluang, Bangkok 10250, Thailand Tel: +66 (0)2 717 1843, Fax: +66(0)2 717 1844 infoasia@widecorp.com

**Foreseeson Custom Displays, Inc.** 2210 E. Winston Road Anaheim, CA 92806 USA Tel: +1 714 300 0540 Fax: +1 714 300 0546

**Foreseeson GmbH** Industriestrasse 38a 63150 Heusenstamm, Germany Tel: +49 6104 64398 0 Fax: +49 6104 64398 11 sales@fsnmed.eu

**Foreseeson UK Ltd.** Unit 2 Kingsmill Business Park Chapel Mill Road Kingston upon Thames Surrey KT1 3GZ Tel: +44 (0) 208 546 1047 sales@fsnmed.eu

Specifications and features are subject to change without notice. Images shown are for illustrative purpose only. All products names are trademarks or registered trademarks of WIDE Corp. This document is copyrighted. Neither this document, nor any part of it, may be reproduced or copied without written permission of WIDE Corp. | Printed in Korea. 2014. 09. Ver 1.1